

I-7560

USB to RS-232/RS-422/RS-485 Converter

Description

The I-7560 is a low-cost module for transferring serial data from a USB port. The I-7560 allows you to connect an RS-232 serial device to the PC using a USB interface. When the I-7560 is connected to a PC, you get a full featured RS-232 port with the familiar PC 9-pin DE connector. The included driver creates a virtual COM port in the PC so your existing programs can communicate with your RS-232 device. The I-7560 module derives its power from the USB port and doesn't need a power adapter. The I-7560 features a high-speed 115.2 Kb/s transmission rate and includes drivers for Windows 98/Me/2K /XP and Linux.



I-7560

- USB 1.1 Compatible
Works with all PCs
- Full RS-232 Output
Duplicates standard PC COM port.
- 300-115200 baud.
Handles high data rates.
- Connects to any RS-232 device.
Provides a RS-232 port for PCs that need a extra RS-232 COM port.
- Includes USB Cable, Windows 98/Me/2K/XP and Linux driver, and manual on CD ROM.
Nothing more to buy!



7560 Model Usage

The I-7560 is a USB Plug&Play device that adds a serial port to any WIN or Linux PC with a USB port. Drivers are included for Microsoft Windows 98/ME/2K/XP and Linux.

Typical Connections

The USB connection is via a 6-foot USB cable to a USB 'B' plug. The RS-232 serial connections are made on the same male 9-pin connector found on the back of a PC. Connect the I-7560 to your existing serial cable or plug it directly onto your serial device.

The I-7560 provides all 9 RS-232 lines found on a PC COM port. The included driver lets you create a virtual COM port. The COM port number can be reassigned to any valid COM port number on Win 2K/XP and Linux systems.



Serial Interfaces

RS-232 Interfaces:

Signals	TX, RX, RTS, CTS, DSR, DTR, DCD, RI and GND
Baud Rates	Std Windows rates up to 115.2 kbaud
Data Bits	7 or 8 bits
Parity	None, odd or even
Stop bits	1 or 2
Flow Cntl	Set by user's program

Physical

Size	123mm x 72mm x 33 mm (without mounting bracket)
Connectors	USB B RS-232 DE-9P
Isolation	none
Temperature	
Operating	-25 °C to 75 °C
Storage	-25 °C to 80 °C
Relative humidity	5 to 95% (not condensing)

ORDERING INFORMATION

USB Module with RS-232 port

Part Number

I-7560